

**UNITED STATES PATENT APPLICATION FOR:**

**AN APPARATUS FOR CONNECTING TUBLARS USING A TOP DRIVE**


**INVENTORS:**

**BERND-GEORG PIETRAS**

**ATTORNEY DOCKET NUMBER: MRKS/0028.C1**

**CERTIFICATION OF MAILING UNDER 37 C.F.R. 1.10**

I hereby certify that this New Application and the documents referred to as enclosed therein are being deposited with the United States Postal Service on March \_\_, 2004, in an envelope marked as "Express Mail United States Postal Service", Mailing Label No. EV416700973US, addressed to: Commissioner for Patents, Mail Stop PATENT APPLICATION, P.O. Box 1450, Alexandria, VA 22313-1450

  
\_\_\_\_\_  
Signature

William B. Patterson  
\_\_\_\_\_  
Name

16 March 2004  
\_\_\_\_\_  
Date of signature

## **AN APPARATUS FOR CONNECTING TUBLARS USING A TOP DRIVE**

### **CROSS-REFERENCE TO RELATED APPLICATIONS**

[0001] This application is a continuation of co-pending U.S. patent application Serial No. 09/762,606, filed May 21, 2001, which is the National Stage of International Application No. PCT/GB99/02708, filed August 16, 1999, which claims benefit of Great Britain Patent Application No. GB9818360.1, filed August 24, 1988. Each of the aforementioned related patent applications is herein incorporated by reference.

### **BACKGROUND OF THE INVENTION**

#### **Field of the Invention**

[0002] This invention relates to an apparatus for facilitating the connection of tubulars using a top drive and is more particularly, but not exclusively, intended for facilitating the connection of a section or stand of casing to a string of casing.

### **SUMMARY OF THE INVENTION**

[0003] In the construction of oil or gas wells it is usually necessary to line the borehole with a string of tubulars known as a casing. Because of the length of the casing required, sections or stands of say two sections of casing are progressively added to the string as it is lowered into the well from a drilling platform. In particular, when it is desired to add a section or stand of casing the string is usually restrained from falling into the well by applying the slips of a spider located in the floor of the drilling platform. The new section or stand of casing is then moved from a rack to the well centre above the spider. The threaded pin of the section or stand of casing to be connected is then located over the threaded box of the casing in the well and the connection is made up by rotation there between. An elevator is then connected to the top of the new section or stand and the whole casing string lifted slightly to enable the slips of the spider to be released. The whole casing string is then lowered until the top of the section is adjacent the spider whereupon the slips of the spider are re-applied, the elevator disconnected and the process repeated.

[0004] It is common practice to use a power tong to torque the connection up to a predetermined torque in order to make the connection. The power tong is located on a platform, either on rails, or hung from a derrick on a chain. However, it has recently been proposed to use a top drive for making such connection. The normal use of such a top drive maybe the driving of a drill string.

[0005] A problem associated with using a top drive for rotating tubulars in order to obtain a connection between tubulars is that some top drives are not specifically designed for rotating tubulars are not able to rotate at the correct speed or have non standard rotors.

[0006] According to the present invention there is provided an apparatus for facilitating the connection of tubulars using a top drive, said apparatus comprising a motor for rotating a tool for drivingly engaging a tubular, and means for connecting said motor to said top drive, the apparatus being such that, in use, said motor can rotate one tubular with respect to another to connect said tubulars.

[0007] Other features of the invention are set out in Claims 2 et seq.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

[0008] For a better understanding of the present invention and in order to show how the same may be carried into effect reference will now be made, by way of example, to the accompanying drawings, in which:

[0009] Figure 1 is a front perspective view of an apparatus in accordance with the present invention; and

[0010] Figure 2 is a rear perspective view of the apparatus of Figure 1 in use.

### **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT**

[0011] Referring to Figure 1 there is shown an apparatus which is generally identified by reference numeral 1.

PATENT

Attorney Docket No.: MRKS/0028.C1

Express Mail No.: EV416700973US

[0012] The apparatus 1 comprises a connecting tubular 2, a suspension unit 3 and a hydraulic motor 4 and 4'. The hydraulic motor 4,4' has a stator 5 and a rotor 6 and is driven by a supply of pressurised hydraulic fluid (the fluid supply lines are not illustrated in the Figures). The suspension unit 3 suspends the hydraulic motor 4,4' from the connecting tubular 2.

[0013] The suspension unit 3 comprises a plate 7 which is fixed to the connecting tubular 2 by a collar 8. The plate 7 has two projections 9 and 10 which have holes 11 and 12 for accommodating axles 13 and 14, which are rotationally disposed therein. The axles 13 and 14 are integral with a rigid body 15. A slider 16 is arranged on runners 17 and (not shown) on the rigid body 15. Arms 18 and 19 are connected at one end to the slider 16 via spherical bearings 20 and at the other end to each side of the stator 5 via spherical bearings 21 and 21'. The arms 18 and 19 are provided with lugs 22 and 22' to which one end of a piston and cylinder 23, 24 is attached and are movable thereabout. The other end of each piston and cylinder 23, 24 is attached to lugs 25, 26 respectively and is movable thereabout. A mud pipe 27 is provided between the plate 7 and the stator 5 for carrying mud to the inside of a tubular therebelow. The mud pipe 27 comprises curved outer surfaces at both ends (not shown) which are located in corresponding recesses in cylindrical sections 28, 29, thus allowing a ball and socket type movement between the plate 7 and the stator 5.

[0014] Referring to Figure 2, the apparatus 1 is suspended from a top drive (not shown) via connecting shaft 2. A tool 30 for engaging with a tubular is suspended from beneath the rotor 6 of the hydraulic motor 4. Such a tool may be arranged to be inserted into the upper end of the tubular, with gripping elements of the tool being radially displaceable for engagement with the inner wall of the tubular so as to secure the tubular to the tool.

[0015] In use, a tubular (not shown) to be connected to a tubular string held in a spider (not shown) is located over the tool 30. The tool 30 grips the tubular. The apparatus 1 and the tubular are lowered by moving the top drive so that the tubular is in close proximity with the tubular string held in the spider. However, due to

PATENT

Attorney Docket No.: MRKS/0028.C1

Express Mail No.: EV416700973US

amongst other things manufacturing tolerances in the tubulars, the tubular often does not align perfectly with the tubular held in the spider. The suspension unit 3 allows minor vertical and horizontal movements to be made by using alignment pistons 31 and 32 for horizontal movements, and piston and cylinders 23 and 24 for vertical movements. The alignment piston 31 acts between the rigid body 15 and the plate 7. The alignment piston 32 acts between the slider 16 and the arm 19. The alignment pistons 31 and 32 and pistons and cylinders 23, 25 are actuated by hydraulic or pneumatic means and controlled from a remote control device.

[0016] The piston and cylinders 23, 24 are hydraulically operable. It is envisaged however, that the piston and cylinders 23, 24 may be of the pneumatic compensating type, i.e. their internal pressure may be adjusted to compensate for the weight of the tubular so that movement of the tubular may be conducted with minimal force. This can conveniently be achieved by introducing pneumatic fluid into the piston and cylinder 23, 24 and adjusting the pressure therein.

[0017] Once the tubulars are aligned, the hydraulic motor 4 and 4' rotate the tubular via 15 gearing in the stator 5 thereby making up the severed connection. During connection the compensating piston and cylinders 23, 24 expand to accommodate the movement of the upper tubular. The alignment pistons 31 and 32 can then be used to move the top of the tubular into alignment with the top drive. If necessary, final torquing can be conducted by the top drive at this stage, via rotation of the pipe 27, and the main elevator can also be swung onto and connected to the tubular prior to releasing the slips in the spider and lowering the casing string. It will be appreciated that the suspension unit 3 effectively provides an adapter for connecting a top drive to the tubular engaging tool 30.